"Echo" Interior Self Amplified Speaker ELK-870

APPLICATION

The ELK-870 is a self amplified interior speaker which may be connected to virtually any audio source, ie: microphone, radio, computer sound card, telephone PBX or KEY system paging output, etc., even an ordinary single line phone set. The audio source is amplified up to 10 watts, adjustable from an onboard volume control. The ELK-870 features a reverse mounted, high quality internal speaker that effectively echos the sound off the surrounding mounting surface. This arrangement enriches the low frequency ranges and reduces the undesirable high "tinny" frequencies. The attractive "no-grille" surface of the ELK-870 may be painted or wallpapered to match the surrounding decor. It is wall or ceiling mountable. For additional coverage, up to three (3) external 8 Ohm speakers may be wired in parallel with the internal speaker. The ELK-870 operates on 12 to 24 Volts A.C. or D.C. and requires only 22-24 gauge telco or alarm type wire.

FEATURES:

- · Self-Contained 10 Watt Amplified Speaker.
- · Amplifies Virtually Any Audio Source.
- · Expanded Telephone System Paging.
- Does Not Require 25 or 70V Line Transformers.
- Attractive "No-Grille" Surface Mount Enclosure.
- May be Painted or Wallpapered.
- Drives Up to Three (3) Additional 8 Ohm Speakers.
- · Built-in Volume Control & Gain Select.
- · Electrical "J" Box Mounting Holes.
- Mounting Hardware Included.

SPECIFICATIONS:

- Operating Voltage: 12 to 24V A.C. or D.C.
- Input Impedance: 1000 Ohms Nominal.
- Audio Input Level: -15 dBm to +10 dBm.
- Rated Output: 10 Watts.
- · Output Speaker Load: 2 to 16 Ohms.
- Current Draw: 38 800 mA Depending on Load and Volume Settings.
- Temperature: 0 to 130°F.
- Humidity: 0 to 95% Non-Precipitating.
- Lifetime Limited Warranty.
- Patent Pending.

Features and Specifications subject to change without notice.



INSTALLATION for ELK-870

- 1. Remove the front cover by inserting and twisting the tip of a wide flat-blade screwdriver in the slots along the edge of the housing.
- 2. Mounting holes are provided on the backplate for a standard electrical J-box as well or for direct surface mounting (hardware included).
- 3. Connect all wiring as follows. Recommended wire gauge is 22-24 AWG. If distance exceeds 1000' use 18-20 guage.

PWR IN: Connect a good quality 12 to 24 Volt A.C. or D.C. power source. No polarity need be observed.

AUDIO IN: Connect an audio input source. ie: microphone, radio, computer sound card, telephone PBX or KEY system paging output, etc.,

even an ordinary single line phone set (see diagram below). With Jumper JP1 set in the NO PREAMP position the ELK-870 is setup for an audio signal of -15 dbm to + 10 dbm. This jumper may be placed in the PREAMP position to provide +18dbm addition

gain for weak audio input signals

SPKR: Internal speaker already connected. The ELK-870 speaker output can handle up to a maximum load of two (2) Ohms. Up to three

(3) additional 8 Ohm speakers (MIN = 20 Watt (ELK-70, ELK-14, ELK-1...) may be connected in parallel on these two terminals.

Recommended ELK-870 Spacing For Background Paging Applications

Ambient Sound Level	Location	Speaker Spacing
Quiet 50 to 65db	Offices	120 feet (14,400 sq. feet)
Moderate 65 to 80db	Light manufacturing	90 feet (8,100 sq. feet)
Noisy 80 to 90db	Heavy manufacturing	60 feet (3,600 sq. feet)
Very Noisy +90cb		40 feet (1,600 sq. feet)

VOLUME: Turn the volume control clockwise (CW) to increase volume. Adjust to a comfortable level.

PREAMP: If the audio input signal is too low for proper amplification, place Jumper JP1 into the PREAMP position for an additional audio


input gain of +18 dbm (8 X gain).

_ 1,000 Ohm 1/2 Watt Resistor

12 to 24 Volts DC ONLY

DO NOT CONNECT TO TELCO LINES

> GREEN RED •



Audio Source

12 to 24 Volts

EXAMPLE 1: BASIC PUBLIC ADDRESS "PA" SYSTEM (using the ELK-870 and a plain Telephone)

FIGURE 1: WIRING HOOKUP

LIFETIME LIMITED WARRANTY

Elk Products, Inc. ("Manufacturer") warrants to the original purchaser (the "Customer") that the products it manufactures ("Product") shall be free from defects in material and workmanship at time of shipment. Manufacturer's obligations under this Limited Warranty shall be limited to repairing or replacing, at its option, free of charge, any product returned to Manufacturer freight prepaid. Manufacturer shall have no obligation under this Limited Warranty or otherwise if (1) the Product has been damaged by negligence, accident, mishandling, lightning or flood, or other Acts of God, (2) the Product has not been operated in accordance with its operating instructions, (3) the Product has been altered or repaired by anyone outside Manufacturer's authorized facilities (4) adaptations or accessories have been made or attached to the Product which, in Manufacturer's sole determination, have adversely affected its performance, safety or reliability. Products such as batteries and fused transformers have their own warranties, and are not included in this Limited Warranty.

If a Product should malfunction or fail, contact Manufacturer or one of its authorized distributors for a Return Authorization (RA) number. Returned Products must include a complete description of the problem, along with the RA number clearly marked on outside of the package. Manufacturer will not be responsible for any unnecessary items included with any returned Product.

THIS WARRANTY IS THE EXCLUSIVE WARRANTY FOR ANY PRODUCT. MANUFACTURER SPECIFICALLY DISCLAIMS ANY AND ALL OTHER WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR OF MERCHANTABILITY. MANUFACTURER SHALL NOT BE LIABLE IN TORT, INCLUDING NEGLIGENCE OR STRICT LIABILITY, AND SHALL HAVE NO LIABILITY AT ALL FOR INJURY TO PERSONS OR PROPERTY. MANUFACTURER'S LIABILITY FOR FAILURE TO FULFILL ITS OBLIGATION UNDER THIS LIMITED WARRANTY OR ANY OTHER LIABILITY IN CONNECTION WITH A PRODUCT SHALL BE LIMITED TO THE AMOUNT OF THE PURCHASE PRICE RECEIVED BY MANUFACTURER FOR THE PRODUCT. THE REMEDIES STATED IN THIS LIMITED WARRANTY ARE THE CUSTOMER'S EXCLUSIVE REMEDIES AGAINST MANUFACTURER REGARDING ANY PRODUCT. UNDER NO CIRCUMSTANCES SHALL MANUFACTURER BE LIABLE FOR ANY INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES, INCLUDING LOST PROFITS AND REVENUES, INCONVENIENCE OR INTERRUPTIONS IN OPERATIONS, OR ANY OTHER COMMERCIAL OR ECONOMIC LOSSES OF ANY KIND. THESE LIMITATIONS AND DISCLAIMERS ARE NOT MADE BY MANUFACTURER WHERE PROHIBITED BY LAW. SOME STATES PROHIBIT LIMITATIONS OF WARRANTIES AND THE CUSTOMER MAY HAVE ADDITIONAL RIGHTS IN THOSE STATES.

For more information contact your local Distributor or: ELK Products, Inc. - PO BOX 100 - 3266 US Hwy. 70 West - Hildebran, NC, - 28637 - USA - 828-397-4200